



# Antique BarnPlank Scar'dFace Flooring

October 1, 2009

## product information

this antique wood was previously used as siding boards on barns; the original rough sawn texture has been tempered by decades of weathering which tend to remove the softer portions of the wood; the Scar'dFace product is planed and sanded to peel back the weathering to produce a mostly smooth floor while retaining the bleed through effects of the aging process; nail holes and knots provide a little more obvious evidence of the floor's previous life; this floor is moderately rustic and is perfectly at home in the country, mountains, desert or even the old American West; with a very soft surface, the floor will continue to show its age as it is put in use in its second life

## specie

predominately pines and hemlock

## source :: antique 100% recycled

primarily siding from barns

## moisture content

kiln-dried to 6-8% moisture content

## hardness

janka hardness rating: 500 averaged

## character rating

our character rating: 6.6 (rustic elements)

our character scale rates floors on a 1 - 10 scale; a low number is a refined floor and a high number is very rustic

## grading

the appearance standards outlined here apply to a floor as a whole and not to individual boards

## knots

an unlimited amount of knots of any size are allowed; some knots are broken and will need filled or defected out by the installer

## holes

an unlimited amount of nail holes are allowed, but generally there are only a few nail holes per board; occasionally bolt holes will also be present that will need filled or defected out by the installer

## cracks/checks

much of the desired character of this product comes from checks in the surface of the boards so an unlimited amount of checking is allowed; cracks through the thickness of the board are allowed as long the board is stable enough for nail down installation

## color

the color variances are unlimited, but predominately range from dark brown to tan, occasionally with a slight red tint

## grain

the majority of the wood will be flat or cathedral grain; some rift cut or quarter sawn boards may be included

## millwork

¾" thick; the tongue and groove will be milled on the edges; the back of the board is milled with back outs; the ends of the boards will be cut square

## widths

6" to 9" faces milled on the ¾" for best yield; floors are produced with a combination of 3 or more face sizes with enough of each size to create a random pattern

## lengths

2' through 10'; with an average length of about 6'; boards up to 12' included if available

**surface**

the face is planed smooth and sanded, but will still have variances from critter tracks, checks and occasional remnants of saw marks

**installation**

basic principles of installation for solid wood floors apply to this product and it should be installed according to the standard professional practices of your area; although, installers should be well experienced with custom wood floors and have artistic skill in board placement

**unfinished**

this flooring product comes unfinished and is designed to be prepped and finished on site