



# Antique Douglas Fir Scar'dFace Flooring

October 1, 2009

## product information

the wood for the Antique Douglas Fir Scar'dFace product usually comes from joists and timbers salvaged from old lumber mills and warehouses; the flooring will have a milled face which reveals the beautiful color and texture of the wood with its striking grain patterns; a knots dance throughout the floor along with a few nail holes surrounded by ferrous bleed from the nails themselves

## specie

primarily Douglas Fir

## source :: antique 100% recycled

industrial salvage

## moisture content

kiln-dried to 6-8% moisture content

## hardness

janka hardness rating: 700

## character rating

our character rating: 5.6 (ample character)

our character scale rates floors on a 1 - 10 scale; a low number is a refined floor and a high number is very rustic

## grading

the appearance standards outlined here apply to a floor as a whole and not to individual boards

## knots

knots are limited to 2" diameter and smaller with no more than one knot per square foot of flooring; some knots may be broken

## holes

occasional nail holes allowed, many with ferrous bleed; rarely bolt holes may be included

## cracks/checks

moderate surface checking is allowed; cracks through the thickness of the board are not allowed

## color

color variation are unlimited, but predominately range from amber to tan and yellow

## grain

the majority of the wood will be flat or cathedral grain; some rift cut or quarter sawn boards may be included

## millwork

¾" thick; the tongue and groove will be milled on the edges; the back of the board is milled with back outs; the ends of the boards will be cut square

## widths

3" to 8" milled to the full inch wide with custom sizes available; floors are usually produced with a combination of 3 or more face sizes with enough of each size to create a random pattern

## lengths

1' through 10'; with an average length of about 6'; boards up to 12' included if available

## surface

the face is planed smooth

## installation

basic principles of installation for solid wood floors apply to this product and it should be installed according to the standard professional practices of your area; although, installers should be well experienced with custom wood floors and have artistic skill in board placement

## unfinished

this flooring product comes unfinished and is designed to be prepped and finished on site