



Antique White Oak Scar'dFace Flooring

November 1, 2009

product information

this white oak flooring is milled from barn timbers and mow logs; the rich color of the wood is nicely accented by worm tracking, knots and occasional nail holes

specie

white oak (with up to 10% allowance for similar appearing boards in other specie)

source :: antique 100% recycled

timbers and mow logs from barns

moisture content

kiln-dried to 6-8% moisture content

hardness

janka hardness rating: 1360

character rating

our character rating: 6.5 (rustic elements)

our character scale rates floors on a 1 - 10 scale; a low number is a refined floor and a high number is very rustic

grading

the appearance standards outlined here apply to a floor as a whole and not to individual boards

knots

an unlimited amount of knots of any size are allowed; some knots are broken and will need filled or defected out by the installer

holes

an unlimited amount of nail holes are allowed, but generally there are very few; occasionally bolt holes will also be present that will need filled or defected out by the installer

cracks/checks

much of the desired character of this product comes from checks in the surface of the boards so an unlimited amount of checking is allowed; cracks through the thickness of the board are allowed as long the board is stable enough for nail down installation

color

the color variances are unlimited, but predominately range from nutmeg brown to tan

grain

the majority of the wood will be flat or cathedral grain; some rift cut or quarter sawn boards may be included

millwork

¾" thick; the tongue and groove will be milled on the edges; the back of the board is milled with back outs; the ends of the boards will be cut square

widths

3" to 7" milled to the full inch wide with custom sizes available; floors are usually produced with a combination of 3 or more face sizes with enough of each size to create a random pattern

lengths

2' through 10'; with an average length of about 6'; boards up to 12' included if available

surface

the face is planed mostly smooth and sanded, but will still have variances from critter tracks, checks and remnants of weathering and saw marks

installation

basic principles of installation for solid wood floors apply to this product and it should be installed according to the standard professional practices of your area; although, installers should be well experienced with custom wood floors and have artistic skill in board placement

unfinished

this flooring product comes unfinished and is designed to be prepped and finished on site