



Reclaimed Mushroom Cypress Scar'dFace Flooring

March 1, 2009

product information

unlike our other Mushroom wood options the Reclaimed Mushroom Cypress Scar'dFace Flooring is quite refined; the smooth grain of the cypress shows through along with the warm, rich color; you will see only a few remnants of saw marks that don't seem to make the floor rustic, rather, more real and rich; make no mistake, this floor comes from the same boards as its more rustic counterpart, but through careful millwork a powerful and refined product is created

specie

predominately Cypress

source :: reclaimed

100% recycled
bunk material from mushroom growing facilities

moisture content

kiln-dried to 6-8% moisture content

hardness

janka hardness rating: 500

character rating

our character rating: 5.5 (ample character)

our character scale rates floors on a 1 - 10 scale; a low number is a refined floor and a high number is very rustic

grade scope

unless otherwise stated the grade standards apply to an entire floor and not to individual boards which allows for a more natural look even in the refined products

knots

an unlimited amount of knots of any size are allowed; some knots are broken and will need filled or defected out by the installer

holes

very rare fastener holes

cracks/checks

much of the desired character of this product comes from checks in the surface of the boards so an unlimited amount of checking is allowed;

cracks through the thickness of the board are allowed as long the board is stable enough for nail down installation

color

the face color will usually vary from very dark brown (almost black when finish is applied) to light golden browns and tans; an unlimited combination of colors is allowed

grain

the majority of the wood will be flat or cathedral grain; some rift cut or quarter sawn boards may be included

millwork

¾" thick; the tongue and groove will be milled on the edges; the back of the board is milled with back outs; the ends of the boards will be cut square

widths

5" to 7" faces milled on the ¾" for best yield; floors are produced with a combination of 3 or more face sizes with enough of each size to create a random pattern

lengths

2' through 12' with an average length of about 8'

surface

the face is planed smooth and sanded, but will still have variances from checks and occasional remnants of saw marks

installation

basic principles of installation for solid wood floors apply to this product and it should be installed according to the standard professional practices of your area; although, installers should be well experienced with custom wood floors and have artistic skill in board placement

unfinished

this flooring product comes unfinished and is designed to be prepped and finished on site